

**Specifications :**


Voltage rating: 600V AC / DC  
 Current rating: Table  
 Withstanding voltage: 2200V AC/minute  
 Temperature range: -40°C~+105°C  
 Insulation resistance: ≥1000M Ω  
 Contact resistance: ≤5mΩ  
 After environmental testing: ≤10mΩ  
 Material : High conductive Brass  
 Wire Range:AWG#12  
 Insulation O.D.: 1.85mm(Max)  
 Plating method : Blank-Stamping before plating

**X5700 T -PSN -H**

- ① ② ③ ④ ⑤


- ① Series Number
- ② Category: T-terminal
- ③ Material: P-Phosphir bronze
- ④ Plating style:  
SN-Bright tin plating 100u" Min Sn,Ni 50u"Min
- ⑤ Mold No./Mark/Special No.

H-Height (applicable to12 #)




SECTION A-A  
SCALE 1:1

CONDUCTOR CRIMP 12 AWG



SECTION A-A  
SCALE 1:1

CONDUCTOR CRIMP 14/16 AWG



SECTION B-B  
SCALE 2:1

Current rating				
Ckt. Size	2	4	6	8~12
AWG &Metric wire size	21A	18 A	16 A	14 A
12 AWG,4mm <sup>2</sup>				

X5700T-PSN-H	High conductive Brass	X5700H	X5700W
PART NO	Material	Suitable XKB Terminal	Suitable XKB Terminal

广东星坤科技股份有限公司

生	日期
ΔX	日期
ΔX	日期
ΔX	日期
MARK	文件工程章

DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE: Wire to board connector
DWN	DATE	VIEW:	PART NO.:
CHKD	DATE	UNIT: mm/in	DWG NO.: X5700T-XX-X
APPD	DATE	SIZE: A4	WEIGHT · SHEET · REVISION
KKB INDUSTRIAL PRECISION CO., LIMITED			1.0g · 1/1 · A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)