



■ Specifications :

- Voltage rating: 250V AC / DC
- Current rating: 7A AC / DC
- Withstanding voltage: 1500V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: $\geq 1000M \Omega$
- Contact resistance: $\leq 10m\Omega$
- After environmental testing : $\leq 20m\Omega$

X8672 H X-XX X-N2 XX
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No
- ② Category : H-HSG
- ③ Welding Board Angle : Blank-Ordinary
- ④ Row No.-Pin No.: XX-Single Row
- ⑤ Plug the Pin & Special No.
- ⑥ Material: N2-PA66 94V-2
- ⑦ Color : Blank-Natural Color

Poles	Dimensions (mm)		Poles	Dimensions (mm)	
	A	B		A	B
2	3.96	8.62	12	43.56	48.23
3	7.92	12.59	13	47.52	52.19
4	11.88	16.55	14	51.48	56.15
5	15.84	20.51	15	55.44	60.11
6	19.80	24.47	16	59.40	64.07
7	23.76	28.43	17	63.36	68.03
8	27.72	32.39	18	67.32	71.79
9	31.68	36.35	19	71.28	75.95
10	35.64	40.31	20	75.24	79.91
11	39.60	44.27			

X8672H-XX-N2	Nylon 66 UL 94V-2	X8672T	X8672W
PART NO	Material	Suitable XKB Terminal	Suitable XKB Terminal

广东星坤科技股份有限公司

生效

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
ΔX					ANGLAR ±5°
ΔX					L ≤ 4 ±0.2
ΔX					4 < L ≤ 16 ±0.3
					16 < L ≤ 63 ±0.4
					L > 63 ±0.5

REVISIONS

www.xk-dg.cn www.helloxkb.com www.helloxkb.cn

文件工程章

DSND	DATE	SCALE: N/A	MODEL TYPE: X8672H-XX-N2
DWN	DATE	VIEW:	PART NO.: 3.96mm Crimp Style Connectors
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)