






XKB



P.C.B LAYOUT



Specificationsxkb

规格:
 Voltage rating:250V AC/DC
 额定电压: 250V AC/DC
 Current rating:3A AC/DC
 额定电流: 3A AC/DC xkb
 Withstanding voltage:1000V AC/minute
 耐受电压: 1000V AC/分钟
 Temperature range:-25℃+85℃
 温度范围: -25℃+85℃
 Insulation resistance:≥500MΩ
 绝缘电阻: ≥500MΩ
 Contact resistance:≤20mΩ
 接触电阻: ≤20mΩ xkb
 After environmental testing:≤30mΩ
 环境测试后: ≤30兆欧

X8821 W R X-XX SL-NO SN
 ○○○○ ○○○○ ○○○○ ○○○○

- ◎Series No.
- ◎Category:W-WAFER
- ◎Welding Board Angle: R-Right Angle 90°
- ◎Welding Way:Blank-DIP
- ◎Row No.Pin No.: XX-Single Row;
- ◎Plug the Pin&Special No.:
 s-Without Positioning;L-With Lock
- ◎Material: NO-PA66 94V-0
- ◎Plating Category: SN-Bright Tin Plating

Circuits	Dimension mm			Circuits	Dimension mm		
	A	B	C		A	B	C
2	2.50	7.50	6.00	10	22.50	27.50	26.00
3	5.00	10.00	8.50	11	25.00	30.00	28.50
4	7.50	12.50	11.00	12	27.50	32.50	31.00
5	10.00	15.00	13.50	13	30.00	35.00	33.50
6	12.50	17.50	16.00	14	32.50	37.50	36.00
7	15.00	20.00	18.50	15	35.00	40.00	38.50
8	17.50	22.50	21.00				
9	20.00	25.00	23.50				

广东星坤科技股份有限公司

生 日期
 發 日期

文件工程章

REVISIONS	DATE	REVISED	APPROVED	DESCRIPTION

DSND	DATE	SCALE: NA	MODEL TYPE:
XKB			X8821WR-XXSL-NO5N
DWN	DATE	VIEW:	PART NO.:
CHKD	DATE	UNIT: mm/mn	2.50mm Crimp Style Connector
APPD	DATE	SIZE: A4	DWG NO.:

X8821WR-XXSL-NO5N	Nylon 66 UL 94V-0	Brass	Tin-Plated	X8821H-L
PART NO	Material	Material(Pin)	Finish(Pin)	Mates With: XKB Housing

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)