



XKB: 2.54[0.100]±0.10

A±0.20

**Specifications:**

规格:  
**Voltage rating:**250V AC/DC  
 额定电压: 250V AC/DC  
**Current rating:** 2A AC/DC  
 额定电流: 2A AC/DC  
**Withstanding voltage:**1500V AC/minute  
 耐压电压: 1500V AC/分钟  
**Temperature range:**25℃~+85℃  
 温度范围: -25℃~+85℃  
**Insulation resistance:**≥1000MΩ  
 绝缘电阻: ≥1000MΩ  
**Contact resistance:** ≤20mΩ  
 接触电阻: ≤20mΩ  
**Linetype:**AWG#22 AWG#24 AWG#26 AWG#28

**X9254 H IR - XX - N0**

- ① ② ③ ④ ⑤  
 ① Series No.  
 ② Category: H-HSG  
 ③ Welding Board Angle: I-HSG+Hardware R-Right Angle 90°  
 ④ Row No.-Pin No.: XX-02P~30P  
 ⑤ Material: N0-PA66 94V-0

Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
2	2.54	5.20	10	22.86	25.52
3	5.08	7.72	11	25.40	28.06
4	7.62	10.28	12	27.94	30.60
5	10.16	12.82	30	73.66	76.32
6	12.70	15.36			
7	15.24	17.90			
8	17.78	20.44			
9	20.32	2.98			

X9254HIR-XX-N0	Nylon 66 UL 94V-0	Brass	Tim-Plated	X9254W
PART NO	Material	Material(Pin)	Finish(Terminal)	Wire Range

广东星坤科技股份有限公司

生 日期

文件工程章

REVISIONS

DATE REVISED APPROVED

UNSPECIFIED TOLERANCES

www.hellixkb.com www.hellixkb.cn

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWVN	DATE	VIEW:	PART NO.: 2.54mm IDC Style Connectors
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	X9254HIR-XX-N0
INDUSTRIAL PRECISION CO., LIMITED			WEIGHT SHEET REVISION
			1.0g 1/1 A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)