




4.20 [0.165]



Recommended P.C.B Layout
General Tolerance±0.05

4.20 [0.165]



Specificationsxxb

规格:

Voltage rating:600V AC/DC

额定电压: 600V AC/DC

Current rating:9A AC/DC

额定电流: 9A AC/DC

Withstanding voltage:1500V AC/minute

耐受电压: 1500V AC/分钟

Temperature

range:-25°C+85°C

温度范围: -25°C+85°C

Insulation resistance:≥100MΩ

绝缘电阻: ≥100MΩ xxb

Contact resistance:≤10mΩ

接触电阻: ≤10mΩ

After environmental

testing:≤20mΩ

环境测试后: ≤20兆欧

X9357WVX-2*XXX-XX XXXX

- ①
- ②
- ③
- ④
- ⑤
- ⑥
- ⑦
- ⑧
- ⑨

- 1 Series No.
- 2 Category:W-AFER
- 3 Welding Board Angle: V- Stright 180°
- 4 Weding Way: Blank-DIP
- 5 Row No Pin No.2*XX-2*01P~2*12P
- 6 Plug the Pin & Special No.:
G-JoinThe glass fiber 15%
- 7 Material: N0-PAG6 94V-0;N2-PA66 94V-2
9T-PA9T94V-0;46-PA46 94V-0
- 8 Plating Category: SN-Bright Tin Plating
- 9 Color:Blank-Natural Color BK-Black GY-Gray

Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
2*01	5.40	-	2*07	30.60	25.20
2*02	9.60	4.20	2*08	34.80	29.40
2*03	13.80	8.40	2*09	39.00	33.60
2*04	18.00	12.60	2*10	43.20	37.80
2*05	22.20	16.80	2*11	47.40	42.00
2*06	26.40	21.00	2*12	51.60	46.20

PART NO	Mistral	Material(Pin)	Finish(Pin)	Suitable XKB Terminal
X9357WV-2XX-9T5W	Nylon 9T UL 94V-0	Brass	Maire bn	
X9357WV-2*XX-N2V01	Nylon 66 UL 94V-2	Brass	Gold-Flash	
X9357WV-2*XX-N2SN	Nylon 66 UL 94V-2	Brass	Tin-Plated	X9357H
X9357WV-2*XX-G-N2V01	Nylon 66 UL 94V-2 GF15%	Brass	Gold-Flash	
X9357WV-2*XX-G-N2SN	Nylon 66 UL 94V-2 GF15%	Brass	Tin-Plated	

广东星坤科技股份有限公司

生	日期
发	
日期	
文件工程章	

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: NA	MODEL TYPE: X9357WV-2*XXX-XXXX
			XKB	ANGLAR ±5°	DWNN	DATE	VIEW: ④	PART NO.:
				L ≤ 4 ±0.2	CHKD	DATE	UNIT: mm/in	4.2 mm Crimp Style Connectors
				4<L≤16 ±0.3	APPD	DATE	SIZE: A4	DWG NO.:
				16<L≤63 ±0.4				
				L > 63 ±0.5				
								WEIGHT
								1.0g
								SHEET
								1/1
								REVISION
								A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)