

Recommended P.C.B Layout
General Tolerance±0.05
XHB Connectivity



Specifications:

规格:
Voltage rating:600V AC/DC
额定电压: 600V AC/DC
Current rating:9A AC/DC
额定电流: 9A AC/DC
Withstanding voltage: 1500V AC/minute
耐受电压: 1500V AC/分钟
Temperature range:-25℃+85℃
温度范围: -25℃+85℃
Insulation resistance:≥1000MΩ
绝缘电阻: ≥1000MΩ
Contact resistance:≤10mΩ
接触电阻: ≤10mΩ
After environmental testing:≤20mΩ
环境测试后: ≤20兆欧

XHB Connectivity

X9357 W/V X-2*XX FS-XX XX XX

- 01 Series No
- 02 Category:W-wafer
- 03 Welding Board Angle:V-Straight 180°
- 04 Welding Way: Blank-DIP
- 05 Row No.-Pin No: 2*XX-Double
- 06 Plug the Pin&Special NO.:
FS-The hollow needle with positioning column
- 07 Material:NO-PA66 94V-0;N2-PA66 94V-2
- 08 Planting Category:SN-Bright tin plating
△ G30-Contact area Gold plating;30u" min;
Tail area Bright tin plating
- 09 Color:Blank-Natural Color



XHB Connectivity

Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
2*01	—	5.60	2*07	25.20	36.80
2*02	4.20	9.80	2*08	29.40	35.00
2*03	8.40	14.00	2*09	33.60	39.20
2*04	12.60	18.20	2*10	37.80	43.40
2*05	16.80	22.40	2*11	42.00	47.60
2*06	21.00	26.60	2*12	46.20	51.80

XHB Connectivity

△ X9357W-V-2*XXFS-NOG30	Nylon 66 UL 94V-2			
X9357W-V-2*XXFS-N2SN	Nylon 66 UL 94V-2	Brass	Tin-Plated	X9357H
X9357W-V-2*XXFS-N0SN	Nylon 66 UL 94V-0			
PART NO	Material	Material(Pin)	Finish(Pin)	Suitable XHB Terminal

广东星坤科技股份有限公司

生 日期
發 日期
文件工程章

REVISIONS	DATE	REVISED	APPROVED

UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: NA	MODEL TYPE:
DWNN	DATE	VIEW:	X9357W-V-2*XXFS-XXXX
CHKD	DATE	UNIT: mm/in	PART NO.: 4.20mm Crimp Style Connector
APPD	DATE	SIZE: A4	DWG NO.:
WPK	DATE	SCALE: NA	REVISION

INDUSTRIAL PRECISION CO., LIMITED

WEIGHT	SHEET	REVISION
1.0g	1/1	A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)