





XKB



Specifications:

规格: XKB
Voltage rating: 600V AC/DC
 额定电压: 600V AC/DC
Current rating: 9A AC/DC
 额定电流: 9A AC/DC
Withstanding voltage: 1500V AC/minute
 耐受电压: 1500V AC/分钟
Temperature range: -25°C→+85°C
 温度范围: -25°C→+85°C
Insulation resistance: ≥1000MΩ
 绝缘电阻: ≥1000MΩ
Contact resistance: ≤10mΩ
 接触电阻: ≤10mΩ
After environmental test fig: ≤20mΩ
 环境测试后: ≤20兆欧

X9357 W V X 2 XX HB -XX SN XX
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪ ⑫ ⑬ ⑭ ⑮ ⑯ ⑰ ⑱ ⑲ ⑳ ㉑ ㉒ ㉓ ㉔ ㉕ ㉖ ㉗ ㉘ ㉙ ㉚ ㉛ ㉜ ㉝ ㉞ ㉟ ㊱ ㊲ ㊳ ㊴ ㊵ ㊶ ㊷ ㊸ ㊹ ㊺ ㊻ ㊼ ㊽ ㊾ ㊿

- 01 Series No
- 02 Category:W-wafer
- 03 Welding Board Angle:V-Straight 180°
- 04 Welding Way:Blank-DIP
- 05 Row No -Pin No: 2*XX-2*02P-2*12P
- 06 Plug-The Pin&Special NO.
- HB-The hollow needle with positioning column arrange ushering
- 07 Material:NO-PA66 94V-0.N2-PA66 94V-7
- 08 Planting Category:SN-Bright tin plating
- 09 Color:Blank-Natural Color

Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
2*02	4.20	15.10	2*08	29.40	40.30
2*03	8.40	19.30	2*09	33.60	44.50
2*04	12.60	23.50	2*10	37.80	48.70
2*05	16.80	27.70	2*11	42.00	52.90
2*06	21.00	31.90	2*12	46.20	57.10
2*07	25.20	36.10			

X9357WV-2*XXHB-N0SN	Nylon 66 UL 94V-0	Brass	Tin-Plated	X9357HM-B
X9357WV-2*XXHB-N2SN	Nylon 66 UL 94V-2	Brass	Tin-Plated	X9357HM-B
PART NO	Material	Material(Pin)	Finish(Pin)	Suitable XKB Terminal

广东星坤科技股份有限公司 P.C.B LAYOUT

生	日期
发	
Δ	
文件	工程章

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DATE	SCALE: N/A	MODEL TYPE: X9357WV-2*XXHB-N0SN
				XKB	DSND		
				ANGLAR ±5°	DWNN	DATE	VIEW: ①
				L ≤ 4 ±0.2	CHKD	DATE	PART NO.: 2.40mm Crimp Style Connectors
				4<L ≤ 16 ±0.3	APPD	DATE	DWG NO.:
				16<L ≤ 63 ±0.4		DATE	UNIT: mm/in
				L > 63 ±0.5		DATE	SIZE: A4
							WEIGHT 1.0g
							SHEET 1/1
							REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)