



**Specifications:**

规格:  
 Voltage rating:250V AC/DC  
 额定电压: 250V AC/DC  
 Current rating:3A AC/DC  
 额定电流: 3A AC/DC  
 Withstanding voltage:600V AC/minute  
 耐受电压:600V AC/分钟  
 Temperature range:-25℃~+85℃  
 温度范围: -25℃~+85℃  
 Insulation resistance:≥1000MΩ  
 绝缘电阻: ≥1000MΩ  
 Contact resistance:≤20mΩ  
 接触电阻: ≤20mΩ  
 After environmental testing:≤30mΩ  
 环境测试后: ≤30兆欧  
 Operating Temperature:-40℃ to +105℃  
 工作温度: -40℃至 +105℃

**X9555WRX-2xXXA-PTV01XX**

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

1. Series No
2. Category:W-WAFER
3. Welding Board Angle:R-Right Angle 90°
4. Welding Way:Blank-DIP
5. Row No-Pin No:2xXX-2x06P-2x64P
6. Plug the Pin&Special NO:A-Ejector Header
7. Material:PT-PBT 94V-0
8. Plating Category:V01-All Gold Flash
9. Color:Blank-Natural Color

poles	Dimensions(mm)		poles	Dimensions(mm)	
	A	B		A	B
2x06	5.08	26.82	2x26	30.48	52.22
2x08	7.60	29.36	2x30	35.56	57.30
2x10	10.16	31.90	2x34	40.64	62.38
2x14	15.24	36.98	2x40	48.26	70.00
2x16	17.78	39.52	2x50	60.96	82.70
2x20	22.86	44.60	2x60	73.66	95.40
2x24	27.94	49.68	2x64	78.74	100.48

X9555WR-2xXXA-PTV01	PBT UL 94V-0	Brass	Gold-Flash	X9555H
PART NO	Material	Material(pin)	Finish(Pin)	Suitable XKB Terminal

广东星坤科技股份有限公司

生效	日期
文件工程章	REVISIONS
DESCRIPTION	DATE
REVISED	APPROVED
UNSPECIFIED TOLERANCES	

units:	mm
tolerance:	
X.X	±0.2mm
X.XX	±0.1mm
X.XXX	±0.05mm

DSND	DATE	SCALE: N/A
DWN	DATE	VIEW: ①
CHKD	DATE	UNIT: mm/in
APPD	DATE	SIZE: A4
XKB INDUSTRIAL PRECISION CO., LIMITED		

MODEL TYPE:	Wire to board connector
PART NO.:	2.54mm Crimp Style Connectors
DWG NO.:	X9555WR-2xXXA-PTV01
WEIGHT	1.0g
SHEET	1/1
REVISION	A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)