



Specifications:

规格:

- Voltage rating:250V AC/DC
- 额定电压: 250V AC/DC
- Current rating:3A AC/DC
- 额定电流: 3A AC/DC
- Withstanding voltage:1500V AC/minute
- 耐受电压: 1500V AC/分钟
- Temperature range:-25℃~+85℃
- 温度范围: -25℃~+85℃
- Insulation resistance:≥1000MΩ
- 绝缘电阻: ≥1000MΩ
- Contact resistance:≤20mΩ
- 接触电阻: ≤20mΩ
- After environmental testing:≤30mΩ
- 环境测试后: ≤30兆欧

X9555 W V XX-2xXX B-6T V01 XX

- ① ②③④ ⑤ ⑥⑦ ⑧ ⑨

- 1.Series No
- 2.Category:W-wafer
- 3.Welding Board Angle:V-180°
- 4.Welding Way:Blank-DIP
- 5.Row No-Pin No:2xXX-Double row
- 6.Special No:
B-DIP=4.10mm Total Length=18.30mm
- 7.Material:6T-PA6T 94V-0
- 8.Planting Category:
VXX:All Gold-Plated GXX:Gold-Plated Contact
X01-Gold Flash; X02-2u";X03-3u";X05-5u"
X10-10u";X15-15u";X30-30u";X50-50u"
SN-Bright tin plating 70u"
SN1-Bright tin plating 120u"Min
SW-Fog Tin plating
- 9.Color:Blank-natural color

X9555WV-2xXXB-6TV01	Nylon 6T UL 94V-0	Brass	Gold-Flash	X9555H
PART NO	Material	Material(Pin)	Finish(Pin)	Suitable XKB Terminal

广东星坤科技股份有限公司 PCB LAYOUT

生	日期
效	
文件	工程
MARK	章

units: mm	DSND	DATE	SCALE: N/A	MODEL TYPE: Wire to board connector
tolerance:	DWN	DATE	VIEW:	PART NO.: 2.00mm Crimp Style Connectors
X.X ±0.2mm	CHKD	DATE	UNIT: mm/in	DWG NO.: X9555WV-2xXXB-6TV01
X.XX ±0.1mm	APPD	DATE	SIZE: A4	WEIGHT 1.0g
X.XXX ±0.05mm				SHEET 1/1
UNSPECIFIED TOLERANCES				REVISION A0

KKB INDUSTRIAL PRECISION CO., LIMITED		
---------------------------------------	--	--

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)