



**Specifications:**

规格:  
 Voltage rating:250V AC/DC  
 额定电压: 250V AC/DC  
 Current rating:3A AC/DC  
 额定电流: 3A AC/DC  
 Withstanding voltage:1500V AC/minute  
 耐受电压: 1500V AC/分钟  
 Temperature range:-25℃~+85℃  
 温度范围: -25℃~+85℃  
 Insulation resistance:≥1000MΩ  
 绝缘电阻: ≥1000MΩ  
 Contact resistance:≤20mΩ  
 接触电阻: ≤20mΩ  
 After environmental testing:≤30mΩ  
 环境测试后: ≤30兆欧

**X9555 W R S-2xXX X-6T V01 XX**

- ① ②③④ ⑤ ⑥⑦ ⑧ ⑨

- 1.Series No
- 2.Category:W-wafer
- 3.Welding Board Angle:V-180°
- 4.Welding Way:S-SMT
- 5.Row No-Pin No:2xXX-Double row
- 6.Special No:
- 7.Material:6T-PA6T 94V-0
- 8.Planting Category:VXX:All Gold-Plated  
X01-Gold Flash
- 9.Color:Blank-Natural Color

poles	Dimensions(mm)			poles	Dimensions(mm)		
	A	B	C		A	B	C
2x02	2.54	12.58	10.28	2x12	27.94	37.98	35.68
2x03	5.08	15.12	12.82	2x13	30.50	40.52	38.22
2x05	10.16	20.20	17.90	2x15	35.56	45.60	43.30
2x06	12.70	22.74	22.44	2x17	40.64	50.68	48.38
2x07	15.24	25.28	22.98	2x20	48.26	58.30	56.00
2x08	17.78	27.82	25.52	2x25	60.86	71.00	68.70
2x09	20.32	30.36	28.06	2x30	73.70	83.70	81.40
2x10	22.86	32.90	30.60	2x32	78.74	88.78	86.48

X9555WWS-2xXX-6TV01	Nylon6T UL 94V-0	Brass	Gold-Flash	X9555H
PART NO	Material	Material(Pin)	Finish(Pin)	Suitable XKB Terminal

广东星坤科技股份有限公司  
 Recommended PCB Layout  
 General Tolerance±0.05

生	日期					units: mm
ΔX						tolerance:
ΔX						X.X ±0.2mm
ΔX						X.XX ±0.1mm
MARK						X.XXX ±0.05mm
文件工程章	DESCRIPTION	DATE	REVISED	APPROVED		UNSPECIFIED TOLERANCES
	REVISIONS					
	www.xk-dg.cn	www.helloxkb.com	www.helloxkb.cn			

DSND		DATE		SCALE: N/A	MODEL TYPE: Wire to board connector	
DWN		DATE		VIEW:	PART NO.:	
CHKD		DATE		UNIT: mm/in	2.54mm Crimp Style Connectors	
APPD		DATE		SIZE: A4	DWG NO.: X9555WWS-2xXX-6TV01	
KKB INDUSTRIAL PRECISION CO., LIMITED				WEIGHT	SHEET	REVISION
				1.0g	1/1	A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)