


SECTION A-A

SCALE 1:1



SECTION B-B

SCALE 1:1

Specifications:

规格:
 Voltage rating:250V AC/DC
 额定电压: 250V AC/DC
 Current rating:3A AC/DC
 额定电流: 3A AC/DC
 Withstanding voltage:1500V AC/minute
 耐受电压: 1500V AC/分钟
 Temperature range:-25℃~+85℃
 温度范围: -25℃~+85℃
 Insulation resistance:≥1000MΩ
 绝缘电阻: ≥1000MΩ
 Contact resistance:≤20mΩ
 接触电阻: ≤20mΩ
 After environmental testing:≤30mΩ
 环境测试后: ≤30兆欧

X9556 T M-B S N
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series Number
- ② Category: T-terminal
- ③ Shape:M-male
- ④ Material:Brass
- ⑤ Plating style:SN-Bright tin plating

广东星坤科技股份有限公司

生	日期
蔡	
文件	工程
章	章

X9556TM-PSN	Brass	AWG#22-28	1.63mm(Max)	Stamping Before Plating 30W Ni70Zn	X9556HF
PART NO	Material	Wire Range	Insulation O.D.	Finish	Suitable XHB

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	PART NO.: 2.54mm Crimp Style Connectors
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	X9556TM-BSN
YKQ INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)