


**Specifications:**

规格: XKB  
**Voltage rating:** 150V AC/DC  
 额定电压: 150V AC/DC  
**Current rating:** 1A AC/DC  
 额定电流: 1A AC/DC  
**Withstanding voltage:** 500V AC/minute  
 耐受电压: 500V AC/分钟  
**Temperature range:** -25°C +85°C  
 温度范围: -25°C +85°C  
**Insulation resistance:**  $\geq 500M\Omega$   
 绝缘电阻:  $\geq 500M\Omega$   
**Contact resistance:**  $\leq 30m\Omega$   
 接触电阻:  $\leq 30m\Omega$   
**After environmental testifg:**  $\leq 40$ 兆欧  
 环境测试后:  $\leq 40$ 兆欧

X9812 T X-P XX X-L

- 01 Series No.
- 02 Category/T-terminal
- 03 Shape/Blank-ordinary
- 04 Material/P-Phosphor bronze
- 05 Plating style/V01-Gold Flash; SN-Brigt tin plating;
- 06 Plating method/Blank-Stamping before plating
- 07 Mold No./Mark/Special No.-Lose



XKB Connectivity

X9812T-PV01-L	Phosphor Bronze	AWG#26-30	1.00mm(Max)	Stamping Before Pating 30u" Ni/Whole Gold Gold Flash	X9812H
X9812T-PSN-L				Stamping Before Pating 30u" Ni/70u"Sn Min	
PART NO	Material	Wire Range	Insulation O.D	Finish	Suitable XKB Terminal

广东星坤科技股份有限公司

生 日期

文件工程章

REVISIONS

DATE REVISED APPROVED

UNSPECIFIED TOLERANCES

www.xkb.cn www.helloxkb.com www.helloxkb.cn

DSND	DATE	SCALE: N/A	MODEL TYPE: X9812T-PSN-L
DWNN	DATE	VIEW:	PART NO.: 1.25mm Crimp Style Connector
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
INDUSTRIAL PRECISION CO., LIMITED			WEIGHT: 1.0g
			SHEET: 1/1
			REVISION: A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)