



Specifications:

规格: **XKB**  
 Voltage rating: 150V AC/DC  
 额定电压: 150V AC/DC  
 Current rating: 1A AC/DC  
 额定电流: 1A AC/DC  
 Withstanding voltage: 500V AC/minute  
 耐受电压: 500V AC/分钟  
 Temperature range: -25°C~+85°C  
 温度范围: -25°C~+85°C  
 Insulation resistance: ≥500MΩ  
 绝缘电阻: ≥500MΩ  
 Contact resistance: ≤30mΩ  
 接触电阻: ≤30mΩ  
 After environmental testing: ≤40mΩ  
 环境测试后: ≤40mΩ

X9812 W V S-2\*XX X-XX V01 XX

- 01 Series No
- 02 Category: W-wafer
- 03 Welding Board Angle: V-Straight 18°
- 04 Welding Way: S-SMT
- 05 Row No.-Pin No: 2\*xx-2\*05P-2\*25P
- 06 Plug the Pin&Special NO.: F-HF
- 07 Material:
  - 6T-PA6T 94V-0 9T-PA9T 94V-0
  - 1T-PA10T 94V-0
- 08 Planting Category: V01-Gold Flash
- 09 Color: Blank-Natural Color

Poles	Dimensions(mm)			
	A	B	C	D
2*05	5.00	12.50	8.15	7.50
2*06	6.25	13.75	9.40	8.75
2*07	7.50	15.00	10.65	10.00
2*10	11.25	18.75	14.40	13.75
2*12	13.75	21.25	16.90	16.25
2*15	17.50	25.00	20.65	20.00
2*20	23.75	31.25	26.90	26.25
2*25	30.00	37.50	33.15	32.50

广东星坤科技股份有限公司  
 Recommended P.C.B Layout  
 General Tolerances: 0.05

生	日期
發	
Δ	
文件	工程章

REVISIONS  
 www.heloxkb.com

XKB	ANGLR	±5°
L ≤ 4	±0.2	
4 < L ≤ 16	±0.3	
16 < L ≤ 63	±0.4	
L > 63	±0.5	

DSND	DATE	SCALE: NA	MODEL TYPE:
DWN	DATE	VIEW:	X9821WVS-2xXX-XXV01
CHKD	DATE	UNIT: mm/in	PART NO.: 2.40mm Crimp Style Connectors
APPD	DATE	SIZE: A4	DWG NO.:
INDUSTRIAL PRECISION CO., LIMITED			WEIGHT: 1.0g
			SHEET: 1/1
			REVISION: A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)