



Recommended P.C.B Oard Hole Layout

■ Specifications :

- Voltage rating: 200V AC / DC
- Current rating: 1A AC / DC
- Withstanding voltage: 500V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥100MΩ
- Contact resistance: ≤40mΩ
- After environmental testing : ≤50mΩ

X9862 W V S-XXA-LP SN

- ① Series No.
- ② Category : W-WAFER
- ③ Welding Board Angle : V-Straight 180°
- ④ Welding Way:S-SMT
- ⑤ Row No.-Pin No.: XX-02P~30P
- ⑥ Plug the Pin&Special NO:A-With Lock
- ⑦ Material : LP-LCP 94V-0
- ⑧ Planting Category:SN-Bright tin plating

PIN	Dimensions(mm)					
	A	B	C	D	E	F
02	1.25	6.10	7.45	2.95	3.75	2.55
03	2.50	7.35	8.70	4.20	5.00	3.80
04	3.75	8.60	9.95	5.45	6.25	5.05
05	5.00	9.85	11.20	6.70	7.50	
06	6.25	11.10	12.45	7.95	8.75	
07	7.50	12.35	13.70	9.20	10.00	
08	8.75	13.60	14.95	10.45	11.25	
09	10.00	14.85	16.20	11.70	12.50	
10	11.25	16.10	17.45	12.95	13.75	6.30
11	12.50	17.35	18.70	14.20	15.00	
12	13.75	18.60	19.95	15.45	16.25	
13	15.00	19.85	21.20	16.70	17.50	
14	16.25	21.10	22.45	17.95	18.75	
15	17.50	22.35	23.70	19.20	20.00	
16	18.75	23.60	24.95	20.45	21.25	

X9862WVS-XXA-LPSN	LCP UL 94V-0	Brass	Tin-Plated	X9862H-A
PART NO	Material	Material (Pin And Solder Tabs)	Finish (Pin And Solder Tabs)	Suitable X KB Terminal

广东星坤科技股份有限公司

生效

ΔX	日期
ΔX	
ΔX	
MARK	DESCRIPTION

文件工程章

REVISIONS

www.xk-dg.cn www.helloxkb.com www.helloxkb.cn

ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5

UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE: X9862WVS-XXA-LPSN
DWN	DATE	VIEW:	PART NO.: 1.25mm Crimp Style Connectors
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)