



常态：2-3导通 5-6导通
按下：1-2导通 4-5导通

FEATURES

- Light operating force.
- Long term low contact resistance.
- Momentary or latching operation.
- Short stroke 1.9mm to latch.
- Compact spacing on PCB of 7.0mm.

SPECIFICATIONS

1. ELECTRICAL

● Contact rating	0.1A30VDC
● Contact resistance	50mWMax.
● Insulation resistance	100MΩMin.at250VDC
● Dielectric strength	250VAC Min. for 60 sec

2. MECHANICAL AND ENVIRONMENTAL

● Temperature rating	Storage:-25 to +65 Operating:-15 to+55
● Operation force	160+80gf
● Stroke	Lock Stroke:1.9±0.2mm Full Stroke:2.4±0.2mm
● Operating life	full load: 1x10 ⁴ cyclesno load: 1x10 ⁵ cycles
● Contact form	DPDT

PAPT NO	XKB7070-X
OPERATION	W:NO LOCK Z:LOCK

ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK
⑦	Contact	—	2	Phosphor bronze	Plating silvering	——
⑥	Terminal	—	6	Brass	Plating silvering	——
⑤	Spring	—	1	Sus	Natural	——
④	Base	—	1	Pbt		——
③	Crochet Needle	—	1	Sus	Natural	——
②	Cover	—	1	Pom		——
①	Keystake	—	1	Pom		——

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE:
					ANGULAR ±5°	DWN	DATE	VIEW:	KEY SWITCH
ΔX					X.X ±0.2mm	CHKD	DATE	UNIT: mm/in	PART NO.:
ΔX					X.XX ±0.1mm	APPD	DATE	SIZE: A4	DWG NO.:
ΔX					X.XXX ±0.05mm				XKB7070-X
						XKB INDUSTRIAL PRECISION CO.,LIMITED			WEIGHT
									1.0g
									SHEET
									1/1
									REVISION
									A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)