






FREE



PUSH



FEATURES

- 特征
- Light operating force. 轻操作力。
- Long term low contact resistance. 长期接触电阻低。
- Mom entary or latching operation. 固定或闭锁操作。
- Short stroke 2.0mm to latch. 短行程2.0毫米至闭锁。
- Compact spacing on PCB of 8.5mm. PCB上的紧凑间距为8.5mm。

SPECIFICATIONS

1.ELECTRICAL

Contact rating	0.1A,30VDC
Contact resistance	50mWMax.
Insulation resistance	100MWMIn. at 250VDC
Dielectric strength	250VAC Min. for 60 sec.

2.MECHANICAL AND ENVIRONMENTAL

Temperature rating	Operating:-15 to+55 Storage: -25 °C to +65 °C
Operation force	160±80gf
Stroke	Lock Stroke: 2.0±0.2mm Full Stroke: 2.5±0.2mm
Operating life	full load: 1x10 <sup>6</sup> cycles no load: 1 x 10 <sup>7</sup> cycles
Contact form	DPDT

PAPT NO	XKB8585-X-170
OPERATION	W:NO LOCK Z:LOCK

⑦ Contact	— 2	Phosphor bronze	Plating silvering	—		
⑥ Terminal	— 6	Brass	Plating silvering	—		
⑤ Spring	— 1	Sus	Natural	—		
④ Base	— 1	Pbt	—	—		
③ Crochet Needle	— 1	Sus	Natural	—		
② Cover	— 1	Pom	—	—		
① Keystake	— 1	Pom	—	—		
ITEM	PAPT NAMF	TERNO	QTY	MATERIAL	FINISHING	REMARK

广东星坤科技股份有限公司

生	日期		
效			
Δ			
Δ			
MARK	DESCRIPTION		
文件	工程章		
REVISIONS	DATE	REVISED	APPROVED
www.xk.com	www.helloxkb.com	www.helloxkb.cn	

ANGULAR	±5°
X.X	±0.2mm
X.XX	±0.1mm
X.XXX	±0.05mm

UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE: KEY SWITCH
DWN	DATE	VIEW:	PART NO.:
CHKD	DATE	UNIT: mm/in	DWG NO.: XKB8585-X-170
APPD	DATE	SIZE: A4	
YKD INDUSTRIAL PRECISION CO., LIMITED		WEIGHT	SHEET
		1.0g	1/1
		REVISION	
		A0	

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)