

Notes:


- 1.All Dimensions are in millimeters
- 2.Operation voltage: 100 VAC max.
- 3.current rating: 1 Amps max.
- 4.Contact resistance: 100m ohms max
- 5.Insulation resistance: 1000M ohms min. 500 VDC
- 6.Dielectric withstanding voltage: 500 VAC/1minute
- 7.Operating Temperature: -20□ to +60□
- 8.Storage Temperature:-40□ to +70□
- 9.Material see table.
- 10.Total Mating Force: 40N(MAX) at 25mm/minute
- 11.Total Unmating Force: 2N (MIN) at 25 mm/minute
- 12.Single Pin Retation Force: 3.0N(MIN) at 25mm/minute
- 13.THE MARK ① ② ③ FOR QC CHK.

XKSD-001-X

1:SPCC  
5:BRASS

PIN#	NAME	DESCRIPTION
1	DAT3	DATA LINE BIT3
2	CMD	COMMAND/RESPONSE
3	VSS1	SUPPLY VOLTAGE GROUND
4	VDD1	SUPPLY VOLTAGE
5	CLK	CLOCK
6	VSS2	SUPPLY VOLTAGE GROUND
7	DAT0	DATA LINE BIT0
8	DAT1	DATA LINE BIT1
9	DAT2	DATA LINE BIT2
10	CD	CARD DETECT
11	WP	WRITE PROTECT

CIRCUIT:



ITEM	PAPT NAME	QTY	MATERIAL	FINISHING
③	Shell	1	SPCC/BRASS	
②	Terminal	11	COPPER ALLOY	
①	Housing	1	LCP UL 94V-0	WHITE

广东星坤科技股份有限公司

生效日期

文件工程章

REVISIONS

www.hellokb.com www.hellokb.com www.hellokb.com

ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5

UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	SD CARD CONN
CHKD	DATE	UNIT: mm/in	PART NO.:
APPD	DATE	SIZE: A4	DWG NO.:
			XKSD-001-X
		WEIGHT	SHEET
		1.0g	1/1
		REVISION	A0

XKB INDUSTRIAL PRECISION CO., LIMITED

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)