



NOTE:

- 1.ELECTRICAL CHARACTERISTICS
 - 1-1. CURRENT RATE: 1.0A
 - 1-2. CONTACT RESISTANCE: 100 Milliohms MAX
 - 1-3. INSULATION RESISTANCE: 1,000 Megohms MIN.
 - 1-4. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
2. RoHS 2002/95/EC COMPLIANT.

ITEM	PAPT NAMF	QTY	MATERIAL	FINISHING
②	Terminal	6	COPPER ALLOY	
①	Housing	1	HI-TEMP.PLASIC UL 94V-0	BLACK

广东星坤科技股份有限公司

生效日期

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES

文件工程章

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	SIM CARD CONN
CHKD	DATE	UNIT: mm/in	PART NO.:
APPD	DATE	SIZE: A4	DWG NO.: XKSIM-005
XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT SHEET REVISION
			1.0g 1/1 A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)