



产品承认书 SPECIFICATION FOR APPROVAL

客户名称:

CUSTOMER

我司料号:

OUR PART NO.

XRSQ1515-5mH-V-1013

我司品名:

OUR PART NAME

SQ扁平线电感

送样日期:

DATE SAMPLES

数量:

QUANTITY

0PCS

制造确认 MANUFACTURER APPROVE

拟制 DRAWN	审核 CHECKED	确认 APPROVED

客户确认 CUSTOMER APPROVE

客户名称 CUSTOMER NAME:

客户料号 CUSTOMER P/N:

规格型号 DESCRIPTION:

XRSQ1515 5mH 立式 10*13

检查结果: 合格 不合格

签名及盖章:

INSPECT RESULT ACCEPT REJECT

SIGNATURE AND STAMP

说明 REMARK:

如对本承认书内容有异议请提出或标记发送至我司, 本承认书在未收到异议回复时于本承认书提供一周后生效。

东莞市祥如电子有限公司

地址: 广东省东莞市塘厦镇莲湖第一工业区南二横路36号B栋

电话: 0769-86346548 传真: 0769-86346358

邮箱: dgxiangru@126.com

SPECIFICATION FOR APPROVAL

CUSTOMER _____

CUSTOMER 'S PART NO _____

DESCRIPTION _____

XRSQ1515 5mH 立式 10*13

VER _____

A

OUR DRAWING NO _____

XRSQ1515-5mH-V-1013

A REVISION HISTORY

DATE OF	REVISED PROJECT	EDITION	NOTE
2024/04/12	NEW VERSION	A	

Page2/7

PPROVED BY	CHECKED BY	PREPARED BY	UNIT	mm
陈婷	唐文	谢诗珍	DATE	2024/04/12
			REV NO.	A


DONGGUAN XIANGRU ELECTRONICS CO.LTD

SPECIFICATION FOR APPROVAL

CUSTOMER _____
 CUSTOMER 'S PART NO _____
 DESCRIPTION XRSQ1515 5mH 立式 10*13

VER _____ A
 OUR DRAWING NO _____ XRSQ1515-5mH-V-1013

1. APPEARANCE & DIMENSION (UNIT: mm):



NOTE:

1. 产品共模绕制，磁芯与底座需点凡立水固定。
2. 产品需含浸或点胶。
3. 焊点不可高于底座支点。


PPROVED BY	CHECKED BY	PREPARED BY	UNIT	mm
陈 婷	唐 文	谢诗珍	DATE	2024/04/12
			REV NO.	A

DONGGUAN XIANGRU ELECTRONICS CO. LTD

SPECIFICATION FOR APPROVAL

CUSTOMER _____
 CUSTOMER 'S PART NO _____
 DESCRIPTION XRSQ1515 5mH 立式 10*13 _____

VER _____ A _____
 OUR DRAWING NO XRSQ1515-5mH-V-1013 _____



4. WINDING TABLE

ORDER	WIRE SIZE	START	END	TURNS	LAYER	INSULATION	
N1	0.3t×1.5mm UEWH 扁平线	1	2	27TS (REF)	CLOSE		
N2	0.3t×1.5mm UEWH 扁平线	4	3	27TS (REF)	CLOSE		

PPROVED BY	CHECKED BY	PREPARED BY	UNIT	mm
陈 婷	唐 文	谢诗珍	DATE	2024/04/12
			REV NO.	A

SPECIFICATION FOR APPROVAL

CUSTOMER _____

CUSTOMER 'S PART NO _____

VER _____ A

DESCRIPTION _____ XRSQ1515 5mH 立式 10*13

OUR DRAWING NO _____ XRSQ1515-5mH-V-1013

5. ELECTRICAL CHARACTERISTICS:

TEST CONDITION:		TEMPERATURE AT: 25°C ± 5°C WORKING TEMPERATURE: -25°C/+125°C STORAGE TEMPERATURE: -25°C/+40°C HUMIDITY: AT 45-80% RH	
TEST INSTRUMENT	CHENHWA/1062	CHENHWA/1062	CHENHWA/502A
ITEM	INDUCTANCE 1KHz, 0.25Vrms 25°	DIFFERENCE INDUCTANCE 1KHz, 0.25V 25°	DC. RESISTANCE AT 25°C
TERMINAL			
1-2	5mH MIN	0.3mH Max	50mΩ MAX
3-4	5mH MIN	0.3mH Max	50mΩ MAX
TEST INSTRUMENT	E-SUN 19053	E-SUN/19053	
ITEM	HI-POT TEST AC 50/60Hz, 5mA, 3sec	INSULATION RESISTANCE. DC 500V	
TERMINAL			
COIL-COIL	1500V	100M Ω MIN	
COIL-CORE	500V	100M Ω MIN	
Idc		5A	

APPROVED BY	CHECKED BY	PREPARED BY	UNIT	mm
陈婷	唐文	谢诗珍	DATE	2024/04/12
			REV NO.	A

SPECIFICATION FOR APPROVAL

CUSTOMER _____

CUSTOMER 'S PART NO _____

VER _____

A

DESCRIPTION _____

XRSQ1515 5mH 立式 10*13

OUR DRAWING NO _____

XRSQ1515-5mH-V-1013

6. MATERIAL LIST:

No	ITEM	MATERIAL	CLASS	UL NO.	MANUFACTURER	OPT.
1	CORE	XRSQ1515 12K			ACMEElectronics (Guangzhou) Co;Ltd	√
		XRSQ1515 12K			SHANGDONG hengrui magnet technology CO.,LTD	√
		XRSQ1515 12K			DongGuan City JiuXin Magnetic Material Co.,Ltd	√
		XRSQ1515 12K			TengZhou MingJi Magnetism Industry Co., Ltd	√
2	BOBBIN	T375HF	150℃	E59481	CHANG CHUN PLASTICS CO LTD	√
3	WIRE	@* FIWx180	180℃	E234867	SUNTEK HOLDINGS LIMITED	√
		@* UEW180	180℃	E504985	Guangdong Lizewire Electric Technology Co Ltd	√
		@* UEW180	180℃	E518668	DAYANG ELECTRICAL TECHNOLOGY (HEYUAN) CO., LTD	
4	VARNISH	E962	130℃	E335405	ZHUHAI CHANGXIAN NEW MATERIALS TECHNOLOGY CO LTD	√
5	锡	无铅锡条 /Sn99.9			Dongguan City Thousand Island METAL Foil CO LTD	√

Page6/7

PPROVED BY	CHECKED BY	PREPARED BY	UNIT	mm
陈 婷	唐 文	谢诗珍	DATE	2024/04/12
			REV NO.	A

DONGGUAN XIANGRU ELECTRONICS CO.LTD

SPECIFICATION FOR APPROVAL

CUSTOMER _____

CUSTOMER 'S PART NO _____

VER _____ A

DESCRIPTION _____ XRSQ1515 5mH 立式 10*13

OUR DRAWING NO _____ XRSQ1515-5mH-V-1013

7. THE INSPECTION REPORT

ITEM	TEXT SPEC.	1	2	3	4	5
L 值 (1-2)	5mH MIN 1KHZ 0.25V 25°	6.5	6.3	5.8	6.3	6.1
L 值 (3-4)	5mH MIN 1KHZ 0.25V 25°	6.5	6.3	5.8	6.3	6.1
DCR 值 (1-2)	50mΩ MAX AT 25°C	OK	OK	OK	OK	OK
DCR 值 (3-4)	50mΩ MAX AT 25°C	OK	OK	OK	OK	OK
HI-POT AC50/60Hz 5mA 3sec	COIL-COIL: 1500V	OK	OK	OK	OK	OK
	COLI-CORE: 500V	OK	OK	OK	OK	OK

TEST EQUIPMENT

INDUCTANCE	HI-POT	DC. R
CH-3250: ()	E-SUN-19053 (√)	CH-502BC (√)
CH-1062: (√)		
CH-101: ()		

APPROVED BY	CHECKED BY	PREPARED BY	UNIT	mm
陈 婷	唐 文	谢诗珍	DATE	2024/04/12
			REV NO.	A

DONGGUAN XIANGRU ELECTRONICS CO. LTD

单击下面可查看定价，库存，交付和生命周期等信息

[>>XR\(祥如\)](#)