



Plastic-Encapsulate Schottky Barrier Diode
Features

- ◆ High Current Capability
- ◆ Low Forward Voltage Drop
- ◆ Extremely Fast Switching Speed

Mechanical Data

- ◆ Case: SOT-23
- ◆ Epoxy UL: 94V-0
- ◆ Mounting Position: Any
- ◆ High temperature soldering guaranteed: 260°C/10s
- ◆ We declare that the material of product compliant with RoHS requirements and Halogen free


MARKING:

Maximum Ratings & Thermal Characteristics

(Ratings at 25°C ambient temperature unless otherwise specified.)





Characteristics	Symbols	Value	Units
Maximum repetitive peak reverse voltage	V_{RRM}	30	V
Maximum RMS voltage	V_{RMS}	30	V
Maximum DC blocking voltage	V_{DC}	30	V
Maximum average forward rectified current	I_{FM}	200	mA
Peak forward surge current 8.3 ms single half sine-wave	I_{FSM}	600	mA
Typical thermal resistance	$R_{\theta JA}, R_{\theta JC}$	500/360	°C/W
Power Dissipation	P_D	200	mW
Junction Temperature	T_J	125	°C
Storage temperature range	T_{STG}	-50 to +150	°C

Electrical Characteristics

(Ratings at 25°C ambient temperature unless otherwise specified.)

Characteristics	Test Condition	Symbols	Min	Typ	Max	Units
Maximum forward voltage	$I_F = 0.1mA$	V_{F1}	-	-	240	mV
	$I_F = 1.0mA$	V_{F2}	-	-	320	mV
	$I_F = 10mA$	V_{F3}	-	-	400	mV
	$I_F = 30mA$	V_{F4}	-	-	500	mV
	$I_F = 100mA$	V_{F5}	-	-	1000	mV
Maximum reverse breakdown voltage	$I_R = 100\mu A$	V_R	30	-	-	V
Maximum reverse current	$V_R = 25V$	I_R	-	-	2.0	uA
Type junction capacitance	$V_R = 1.0V, f = 1MHz$	C_j	-	-	10	pF
Reverse Recovery time	$I_F = I_R = 10mA, I_{rr} = 0.1 \times I_R, RL = 100\Omega$	trr	-	-	5	ns

Typical characteristics




Package Dimensions

SOT-23

Dim.	Millimeter(mm)		mil	
	Min.	Max.	Min.	Max.
A	0.9	1.15	35	45
A1	0.1		3.9	
bp	0.38	0.48	15	19
C	0.09	0.15	3.54	5.9
D	2.8	3.0	110	118
E	1.2	1.4	47	55
E	1.9		75	
E1	0.95		37	
HE	2.1	2.55	83	100
Lp	0.15	0.45	5.9	18
Q	0.45	0.55	18	22
v	0.2		7.9	
W	0.1		4	

The recommended mounting pad size



Disclaimer

The information presented in this document is for reference only. Guangdong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.

单击下面可查看定价，库存，交付和生命周期等信息

[>>YFW\(佑风微\)](#)