


**Surface Mount Schottky Barrier Rectifier**
**Reverse Voltage - 60 V**
**Forward Current - 5 A**
**FEATURES**

- ◆Metal silicon junction, majority carrier conduction
- ◆For surface mounted applications
- ◆Low power loss, high efficiency
- ◆High forward surge current capability
- ◆For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- ◆Lead free in comply with EU RoHS 2011/65/EU directives

**MECHANICAL DATA**

- ◆Case: SMBF
- ◆Terminals: Solderable per MIL-STD-750, Method 2026
- ◆Approx. Weight: 57mg /0.002oz

**Pinning**

**Marking Code**

<b>SSL56BF</b>	<b>SL56B</b>
----------------	--------------

**Absolute Maximum Ratings and Electrical characteristics**


Ratings at 25 ° ambient temperature unless otherwise specified.Single phase, half wave, 60Hz resistive or inductive load, for capacitive load, derate by 20 %

Parameter	Symbols	SSL56BF	Units
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	60	<b>V</b>
Maximum RMS voltage	$V_{RMS}$	42	<b>V</b>
Maximum DC Blocking Voltage	$V_{DC}$	60	<b>V</b>
Maximum Average Forward Rectified Current	$I_{F(AV)}$	5.0	<b>A</b>
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed On Rated Load (JEDEC method)	$I_{FSM}$	150	<b>A</b>
Maximum Instantaneous Forward Voltage at 5 A	$V_F$	0.50	<b>V</b>
Maximum Instantaneous Reverse Current at Rated DC Reverse Voltage	$I_R$	1 50	<b>mA</b>
Typical Junction Capacitance <sup>(1)</sup>	$C_j$	800	<b>pF</b>
Typical Thermal Resistance <sup>(2)</sup>	$R_{\theta JA}$	40	<b>°C/W</b>
Operating Junction Temperature Range	$T_j$	-55 ~ +150	<b>°C</b>
Storage Temperature Range	$T_{stg}$	-55 ~ +150	<b>°C</b>


(1) Measured at 1 MHz and applied reverse voltage of 4 V D.C

(2) P.C.B. mounted with 2.0" X2.0" (5 X 5 cm) copper pad areas.


**Fig.1 Forward Current Derating Curve**




**Fig.2 Typical Reverse Characteristics**




**Fig.3 Typical Forward Characteristic**




**Fig.4 Typical Junction Capacitance**



**Fig.5 Maximum Non-Repetitive Peak Forward Surge Current**




**Fig.6- Typical Transient Thermal Impedance**



**Package Outline**


**SMBF**

Plastic surface mounted package; 2 leads



UNIT		A	C	D	E	H <sub>E</sub>	e	g	∠
mm	max	1.3	0.26	4.4	3.7	5.5	2.2	1.0	9°
	min	1.1	0.18	4.2	3.5	5.1	1.9		
mil	max	51	10	173	146	216	86	40	
	min	43	7	165	138	200	75		

**The recommended mounting pad size**



**Summary of Packing Options**

Package	Packing Description	Packing Quantity	Industry Standard
SMBF	Tape/Reel, 13" reel	5000	EIA-481-1

单击下面可查看定价，库存，交付和生命周期等信息

[>>YFW\(佑风微\)](#)