


Forward Current - 1 A

FEATURES

- For surface mounted applications
- Low profile package
- Glass Passivated Chip Junction
- Ideal for automated placement
- Lead free in comply with EU RoHS 2011/65/EU directives



MECHANICAL DATA

- Case: SOD-123F
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 14mg

Maximum Ratings and Electrical characteristics






Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.

Parameter	Symbols	1N4001W	Units
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	50	V
Maximum RMS voltage	V _{RMS}	35	V
Maximum DC Blocking Voltage	V _{DC}	50	V
Maximum Average Forward Rectified Current at T _c = 125°C	I _{F(AV)}	1	A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load	I _{FSM}	25	A
Maximum Instantaneous Forward Voltage at 1 A	V _F	1.1	V
Maximum DC Reverse Current T _a = 25 °C at Rated DC Blocking Voltage T _a = 125 °C	I _R	5 50	µA
Typical Junction Capacitance ⁽¹⁾	C _j	11	pF
Typical Thermal Resistance ⁽²⁾	R _{θJA}	90	°C/W
Operating and Storage Temperature Range	T _j , T _{stg}	-55 ~ +150	°C

(1) Measured at 1 MHz and applied reverse voltage of 4 VD.C

(2) P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.



单击下面可查看定价，库存，交付和生命周期等信息

[**>>YONGYUTAI\(永裕泰\)**](#)