




P. C. B LAYOUT

规格:

1. 插入力: 44.1N MAX.
2. 拔出力: 7~25N
3. 耐久性: 10000 CYCLES MIN.
4. 额定电流: 0.5A
5. 额定电压: 40V MAX
6. 耐电压: 500V AC MIN. (UNMATED)
300V AC MIN. (MATED)
7. 接触阻抗: 30mΩ MAX.
8. 绝缘电阻: 100MΩ MIN (UNMATED)
10MΩ MIN (MATED)
9. 工作温度: -20℃ TO +85℃
10. 所用材质须符合RoHS要求

外壳镀金:
HXC12-HDMI A19-610A

 深圳市华宇创精密电子有限公司				
TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5'	DRAWN BY :	DATE :	PART NAME:	
	陈一鸣	2014-02-23	HDMI A TYPE 三排插件	
  UNIT: mm [inch] SCALE: 1:1 SIZE: A4	CHECKED BY :	DATE :	PART NO.	HXC12-HDMI19-610B
	马跃	2014-02-23	MOLD NO.	
	APPROVED BY :	DATE :	DRAW NO:	HXC-HDMI13091102
		2014-02-23	SHEET NO.	1 OF 1

单击下面可查看定价，库存，交付和生命周期等信息

[>>华宇创](#)