

**KEMET Part Number: MMC10.2273J400A31TR16**  
(F160WP273J400V)

MMC/F160, Film, Metallized Polyester, General Purpose, 0.027 uF, 5%, 200 VAC, 400 VDC, 100°C, 4036, 5.5mm



Note: '()' correspond to the letters used in the product bulletin

| Dimensions |                 |
|------------|-----------------|
| Chip Size  | 4036            |
| L          | 10.2mm +/-0.2mm |
| W          | 9.1mm +/-0.2mm  |
| T          | 5.5mm +/-0.2mm  |
| F          | 0.5mm NOM       |

| Packaging Specifications |     |
|--------------------------|-----|
| Packaging:               | T&R |
| Packaging Quantity:      | 800 |

| General Information |                                     |
|---------------------|-------------------------------------|
| Series:             | MMC/F160                            |
| Dielectric:         | Metallized Polyester                |
| Style:              | SMD Chip                            |
| RoHS:               | Yes                                 |
| Miscellaneous:      | Not For New Design. Use Series F161 |

| Specifications         |                                    |
|------------------------|------------------------------------|
| Capacitance:           | 0.027 uF                           |
| Capacitance Tolerance: | 5%                                 |
| Voltage AC:            | 200 VAC                            |
| Voltage DC:            | 400 VDC                            |
| Temperature Range:     | -55/+100C                          |
| Rated Temperature:     | 100°C                              |
| Dissipation Factor:    | 0.8% 1kHz, 1.2% 10kHz, 2.5% 100kHz |
| Insulation Resistance: | 15 GOhms                           |
| Max dV/dt:             | 40 V/us                            |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET Electronics\(基美\)](#)