

**KEMET Part Number: MMC5.7224K50J35BULK**  
(F160PU224K050A)

MMC/F160, Film, Metallized Polyester, General Purpose, 0.22 uF, 10%, 30 VAC, 50 VDC, 100°C, 2220, 4mm



Note: '()' correspond to the letters used in the product bulletin

| Dimensions |                |
|------------|----------------|
| Chip Size  | 2220           |
| L          | 5.7mm +/-0.2mm |
| W          | 5mm +/-0.2mm   |
| T          | 4mm +/-0.2mm   |
| F          | 0.5mm NOM      |

| Packaging Specifications |           |
|--------------------------|-----------|
| Packaging:               | Bulk, Bag |
| Packaging Quantity:      | 2000      |

| General Information |  |
|---------------------|--|
| Series:             | MMC/F160   |
| Dielectric:         | Metallized Polyester                                 |
| Style:              | SMD Chip   |
| RoHS:               | Yes  |
| Miscellaneous:      | Not For New Design. Use F161PU224K050A (Series F161) |

| Specifications         |                                       |
|------------------------|---------------------------------------|
| Capacitance:           | 0.22 uF                               |
| Capacitance Tolerance: | 10%                                   |
| Voltage AC:            | 30 VAC                                |
| Voltage DC:            | 50 VDC                                |
| Temperature Range:     | -55/+100C                             |
| Rated Temperature:     | 100°C                                 |
| Dissipation Factor:    | 0.80% 1kHz, 1.20% 10kHz, 3.00% 100kHz |
| Insulation Resistance: | 15 GOhms                              |
| Max dV/dt:             | 20 V/us                               |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET Electronics\(基美\)](#)