
KEMET Part Number: HT06DN153JN

(HT06DN153J)



HTHP LDD Indust C0G HT200C, Ceramic, 0.015 uF, 5%, 200 VDC, C0G, Commercial, High Temperature, Lead Spacing = 5.08mm



General Information		
Series:	HTHP LDD Indust C0G HT200C	
Style:	Radial	
Description:	Commercial, High Temperature	
Features:	Commercial	
RoHS:	Yes	
Termination:	Nickel	
Failure Rate:	N/A	
AEC-Q200:	No	

Dimensions		
L	7.62mm MAX	
Н	7.62mm MAX	
Т	3.81mm MAX	
S	5.08mm +/-0.76mm	
LL	31.75mm MIN	
F	0.635mm NOM	

Specifications	
Capacitance:	0.015 uF
Capacitance Tolerance:	5%
Voltage DC:	200 VDC
Dielectric Withstanding Voltage:	500 VDC
Temperature Range:	-55/+200°C
Temperature Coefficient:	COG
Dissipation Factor:	0.15%
Insulation Resistance:	66.7 GOhms

Packaging Specifications	
Packaging:	Bulk, Bag
Packaging Quantity:	1

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET Electronics(基美)