

**KEMET Part Number: MMC10.2155J50A31BULK**  
(F160WP155J050A)

MMC/F160, Film, Metallized Polyester, General Purpose, 1.5 uF, 5%, 30 VAC, 50 VDC, 100°C, 4036, 5.5mm



Note: '( )' correspond to the letters used in the product bulletin

Dimensions	
Chip Size	4036
L	10.2mm +/-0.2mm
W	9.1mm +/-0.2mm
T	5.5mm +/-0.2mm
F	0.5mm NOM

Packaging Specifications	
Packaging:	Bulk, Bag
Packaging Quantity:	1000

General Information	
Series:	MMC/F160
Dielectric:	Metallized Polyester
Style:	SMD Chip
RoHS:	Yes
AEC-Q200:	No
Miscellaneous:	Not For New Design. Use Series F161
Shelf Life:	104 Weeks

Specifications	
Capacitance:	1.5 uF
Capacitance Tolerance:	5%
Voltage AC:	30 VAC
Voltage DC:	50 VDC
Temperature Range:	-55/+100C
Rated Temperature:	100°C
Dissipation Factor:	0.80% 1kHz, 1.50% 10kHz
Insulation Resistance:	3.3333 GOhms
Max dV/dt:	12 V/us

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET Electronics\(基美\)](#)