
KEMET Part Number: MMC7.3392K63K31BULK Not for New Design

(F160SG392K063A)



MMC/F160, Film, Metallized Polyester, General Purpose, 3900 pF, 10%, 40 VAC, 63 VDC, 100°C, 2824, 2.5mm



Note: '()' correspond to the letters used in the product bulletin

Dimensions	
Chip Size	2824
L	7.3mm +/-0.2mm
W	6mm +/-0.2mm
Т	2.5mm +/-0.2mm
F	0.5mm NOM

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	2000	

General Information		
Series:	MMC/F160	
Dielectric:	Metallized Polyester	
Style:	SMD Chip	
RoHS:	Yes	
Miscellaneous:	Not For New Design. Use Series F161	
Notes:	Not For New Design	

Specifications		
Capacitance:	3900 pF	
Capacitance Tolerance:	10%	
Voltage AC:	40 VAC	
Voltage DC:	63 VDC	
Temperature Range:	-55/+100C	
Rated Temperature:	100°C	
Dissipation Factor:	0.80% 1kHz, 1.20% 10kHz, 2.50% 100kHz	
Insulation Resistance:	15 GOhms	
Max dV/dt:	50 V/us	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



)64a4

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET Electronics(基美)