

KEMET Part Number: MMC7.3334J50K35TR12
(F160SP334J050V)

MMC/F160, Film, Metallized Polyester, General Purpose, 0.33 uF, 5%, 30 VAC, 50 VDC, 100°C, 2824, 3.5mm



Note: '()' correspond to the letters used in the product bulletin

| Dimensions | |
|------------|----------------|
| Chip Size | 2824 |
| L | 7.3mm +/-0.2mm |
| W | 6mm +/-0.2mm |
| T | 3.5mm +/-0.2mm |
| F | 0.5mm NOM |

| Packaging Specifications | |
|--------------------------|------|
| Packaging: | T&R |
| Packaging Quantity: | 2300 |

| General Information | |
|---------------------|-------------------------------------|
| Series: | MMC/F160 |
| Dielectric: | Metallized Polyester |
| Style: | SMD Chip |
| RoHS: | Yes |
| Miscellaneous: | Not For New Design. Use Series F161 |

| Specifications | |
|------------------------|----------------------------------|
| Capacitance: | 0.33 uF |
| Capacitance Tolerance: | 5% |
| Voltage AC: | 30 VAC |
| Voltage DC: | 50 VDC |
| Temperature Range: | -55/+100C |
| Rated Temperature: | 100°C |
| Dissipation Factor: | 0.8% 1kHz, 1.2% 10kHz, 3% 100kHz |
| Insulation Resistance: | 15 GOhms |
| Max dV/dt: | 25 V/us |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET Electronics\(基美\)](#)