

KEMET Part Number: MMK15105K100B04L3DBULK
(F601BD105K100CL30D)

MMK/F601, Film, Metallized Polyester, General Purpose, 1 uF, 10%, 100 VDC, 85°C, Lead Spacing = 15mm



| Dimensions | |
|------------|---------------|
| L | 18mm MAX |
| H | 10.5mm MAX |
| T | 5.5mm MAX |
| S | 15mm +/-0.4mm |
| LL | 3mm NOM |
| F | 0.8mm NOM |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging: | Bulk, Bag |

| General Information | |
|---------------------|---|
| Series: | MMK/F601 |
| Dielectric: | Metallized Polyester |
| Style: | Radial |
| Features: | DC Multipurpose Applications |
| RoHS: | Yes |
| Lead: | Wire Leads |
| Notes: | Not For New Design, Please Check Possible Alternative Parts (AltPart) |

| Specifications | |
|------------------------|--------------------------|
| Capacitance: | 1 uF |
| Capacitance Tolerance: | 10% |
| Voltage AC: | 63 VAC |
| Voltage DC: | 100 VDC, 77.5 VDC (100C) |
| Temperature Range: | -55/+100C |
| Rated Temperature: | 85°C |
| Insulation Resistance: | 5 GOhms |
| Max dV/dt: | 8 V/us |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET Electronics\(基美\)](#)