
KEMET Part Number: HT55BN272KN

(HT55BN272K)



HTHP LDD Indust C0G HT200C, Ceramic, 2700 pF, 10%, 50 VDC, C0G, Commercial, High Temperature, Lead Spacing = 5.08mm



General Information	
Series:	HTHP LDD Indust C0G HT200C
Style:	Radial
Description:	Commercial, High Temperature
Features:	Commercial
RoHS:	Yes
Termination:	Nickel
Failure Rate:	N/A
AEC-Q200:	No

Dimensions	
L	5.08mm MAX
Н	5.08mm MAX
Т	2.54mm MAX
S	5.08mm +/-0.76mm
LL	31.75mm MIN
F	0.635mm NOM
G	1.65mm MAX

Specifications	
Capacitance:	2700 pF
Capacitance Tolerance:	10%
Voltage DC:	50 VDC
Dielectric Withstanding Voltage:	125 VDC
Temperature Range:	-55/+200°C
Temperature Coefficient:	COG
Dissipation Factor:	0.15%
Insulation Resistance:	100 GOhms

Packaging Specifications	
Packaging:	Bulk, Bag
Packaging Quantity:	1

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generate



879f9

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET Electronics(基美)