
## KEMET Part Number: PFR5151H630J11L4BULK

(F411JH151H630C)



PFR/F411, Film, Film/Foil Polypropylene, 150 pF, 2.5%, 630 VDC, 85°C, Lead Spacing = 5mm



General Information		
Series:	PFR/F411	
Dielectric:	Film/Foil Polypropylene	
Style:	Radial	
Features:	Pulse	
RoHS:	Yes	
Lead:	Wire Leads	
Miscellaneous:	An Operating Temperature Up To +105C Is Allowed Under Certain Conditions. Please Consult KEMET For Details.	

Dimensions		
L	7.2mm MAX	
Н	6mm MAX	
Т	4.5mm MAX	
S	5mm -0.4mm	
LL	4mm +1mm	
F	0.5mm +/-0.05mm	
G	0.5mm NOM	

L	7.2mm MAX
Н	6mm MAX
Т	4.5mm MAX
S	5mm -0.4mm
LL	4mm +1mm
F	0.5mm +/-0.05mm
G	0.5mm NOM

-	0.511111 +/-0.0511111	Rateu Tellip
G	0.5mm NOM	Dissipation
		Insulation Res
5 1 1	0 10 1	Ma
Packaging Specifications		Indu
Packagin	g: Bulk	
Packaging Quantit	y: 1000	

Specifications		
Capacitance:	150 pF	
Capacitance Tolerance:	2.5%	
Voltage AC:	250 VAC	
Voltage DC:	630 VDC	
Temperature Range:	-55/+100C	
Rated Temperature:	85°C	
Dissipation Factor:	0.04% 1kHz, 0.04% 10kHz, 0.05% 100kHz	
Insulation Resistance:	200000 GOhms	
Max dV/dt:	1000 V/us	
Inductance:	6 nH	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET Electronics(基美)