

KEMET Part Number: MMK22.5156K63D16L4BULK
(F601DT156K063CVBLK, MMK22,5156K63D16L4BULK)

MMK/F601, Film, Metallized Polyester, General Purpose, 15 uF, 10%, 63 VDC, 85°C, Lead Spacing = 22.5mm



Dimensions

L	26mm MAX
H	21.5mm MAX
T	11mm MAX
S	22.5mm +/-0.4mm
LL	4mm NOM
F	0.8mm NOM

Packaging Specifications

Packaging:	Bulk, Bag
-------------------	-----------

General Information

Series:	MMK/F601
Dielectric:	Metallized Polyester
Style:	Radial
Features:	DC Multipurpose Applications
RoHS:	Yes
Lead:	Wire Leads
Notes:	Not For New Design, Please Check Possible Alternative Parts (AltPart)

Specifications

Capacitance:	15 uF
Capacitance Tolerance:	10%
Voltage AC:	40 VAC
Voltage DC:	63 VDC, 48.8 VDC (100C)
Temperature Range:	-55/+100C
Rated Temperature:	85°C
Insulation Resistance:	333.3 MOhms
Max dV/dt:	3 V/us

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET Electronics\(基美\)](#)