
KEMET Part Number: MDC10334K400A58P8TUBE

(F158AA334K400T)



MDC, Film, Metallized Polyester, Dual-In-Line, 0.33 uF, 10%, 200 VAC, 400 VDC, 85°C, 10mm



Dimensions	
L	23mm +/-0.2mm
L2	2.61mm +/-0.2mm
W	12.7mm +/-0.2mm
Н	11mm +/-0.2mm
H1	12.5mm +/-0.4mm
S	10mm +/-0.2mm
S1	2.54mm +/-0.2mm
S2	17.78mm +/-0.2mm
LL	1.5mm +/-0.2mm
F	0.5mm +/-0.05mm
E	0.2mm MAX
G	0.3mm MAX
Х	0.35mm +/-0.05mm
Y	1.5mm +/-0.2mm
Z	0mm NOM

Packaging Specifications		
Packaging:	Tube	
Packaging Quantity:	21	

General Information		
Series:	MDC	
Dielectric:	Metallized Polyester	
Style:	Dual-In-Line	
RoHS:	Yes	
Lead:	L Leads	
AEC-Q200:	No	

Specifications		
Capacitance:	0.33 uF	
Capacitance Tolerance:	10%	
Voltage AC:	200 VAC	
Voltage DC:	400 VDC	
Temperature Range:	-55/+125°C	
Rated Temperature:	85°C	
Dissipation Factor:	0.80% 1kHz, 1.50% 10kHz, 5.00% 100kHz	
Insulation Resistance:	30 GOhms	
Inductance:	4 nH	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET Electronics(基美)