


**KEMET Part Number: MDK10334J400A58P8TUBE**  
(F688AA334J400T)

MDK/F68, Film, Metallized Polyester, Dual-In-Line, 0.33 uF, 5%, 200 VAC, 400 VDC, 85°C, 10mm



General Information	
Series:	MDK/F68
Dielectric:	Metallized Polyester
Style:	Dual-In-Line
RoHS:	Yes
Lead:	Wire Leads
AEC-Q200:	No

Specifications	
Capacitance:	0.33 uF
Capacitance Tolerance:	5%
Voltage AC:	200 VAC
Voltage DC:	400 VDC
Temperature Range:	-55/+125°C
Rated Temperature:	85°C
Dissipation Factor:	0.80% 1kHz 1.50% 10kHz 5.00% 100kHz
Insulation Resistance:	30 GOhms
Inductance:	4 nH

Dimensions	
L	23mm +/-0.2mm
L2	2.61mm MAX
W	12.7mm +/-0.2mm
H	11mm +/-0.2mm
S	10mm +/-0.2mm
S1	2.54mm +/-0.2mm
S2	17.78mm +/-0.2mm
LL	3.2mm +1mm
F	0.5mm +/-0.05mm
E	0.2mm MAX
G	0.3mm MAX
X	0.35mm +/-0.05mm

Packaging Specifications	
Packaging:	Tube
Packaging Quantity:	21

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET Electronics\(基美\)](#)