


ALS32, Aluminum Electrolytic, 6,800 uF, 20%, 450 VDC, -40/+85°C



General Information	
Series:	ALS32
Dielectric:	Aluminum Electrolytic
Description:	Screw Terminal, Aluminum Electrolytic
RoHS:	Yes
AEC-Q200:	No
Notes:	Add 0.4mm To D (1.1mm When D = 88.9) And 1.1mm To L For sleeving. MS (MxH) = M12x16. Mounting Clip (Sold Separately): V90
Shelf Life:	156 Weeks

Dimensions	
D	88.9mm +/-0.8mm
L	149.2mm +/-1.6mm
T	5.5mm +/-0.5mm
S	31.8mm +/-0.5mm
DT	13mm +/-0.5mm
LT	154mm +/-1mm
TD	10mm MIN
V	25mm NOM
Z	10mm NOM

Specifications	
Capacitance:	6,800 uF
Capacitance Tolerance:	20%
Voltage DC:	450 VDC, 495 VDC (Surge)
Temperature Range:	-40/+85°C
Rated Temperature:	85°C
Life:	20000 Hrs (Rated Voltage And Ripple Current At 85C), 40000 Hrs (Rated Voltage At 85C)
Resistance:	19 mOhms (120Hz 25C), 13 mOhms (20kHz 25C)
Ripple Current:	24.6 Amps (120Hz 85C), 36.3 Amps (20kHz 85C)
Leakage Current:	6000 uA (5min 20°C)

Packaging Specifications	
Weight:	1.36 kg
Packaging:	Bulk, Box

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET Electronics\(基美\)](#)