
KEMET Part Number: F5ADF4100Z3C2K Not for New Design

(5ADF4100Z3C2K)



F5A, Film, Metallized Polyester, Varistor/Capacitor, 1 uF, 10%, 63 VDC, 100°C, Lead Spacing = 10mm



| General Information | |
|---------------------|-----------------------------|
| Series: | F5A |
| Dielectric: | Metallized Polyester |
| Style: | Radial |
| Features: | EMI-RFI suppressors for DC |
| | motors |
| RoHS: | Yes |
| Lead: | Wire Leads |
| Miscellaneous: | The Rated Voltage Decreases |
| | 2%/C Between +100C And |
| | +125C. Varistor= 68 VDC |

| Dimensions | |
|------------|-----------------|
| L | 13.4mm MAX |
| Н | 11.1mm MAX |
| Т | 5.2mm MAX |
| S | 10mm +/-0.4mm |
| LL | 17mm +1/-2mm |
| F | 0.7mm +/-0.05mm |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging: | Bulk, Bag |
| Packaging Quantity: | 2000 |

| Specifications | | |
|------------------------|-----------------------|--|
| Capacitance: | 1 uF | |
| Capacitance Tolerance: | 10% | |
| Voltage DC: | 63 VDC, 32 VDC (125C) | |
| Temperature Range: | -55/+125°C | |
| Rated Temperature: | 100°C | |
| Dissipation Factor: | 1.00% 1kHz | |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.





单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET Electronics(基美)