KEMET Part Number: C1812W334KCRACTU

(C1812W334KCRAC7800)



ArcShield SMD Comm X7R HV, Ceramic, 0.33 uF, 10%, 500 VDC, X7R, SMD, MLCC, Arcshield, High Voltage, 1812



Dimensions		
L	4.5mm +/-0.4mm	
W	3.2mm +/-0.3mm	
Т	2.1mm +/-0.20mm	
В	0.7mm +/-0.35mm	

Packaging Specifications		
Packaging:	T&R, 180mm, Plastic Tape	
Packaging Quantity:	500	

General Information	
Series:	ArcShield SMD Comm X7R HV
Style:	SMD Chip
Description:	SMD, MLCC, Arcshield, High Voltage
Features:	High Voltage
RoHS:	Yes
Termination:	Flexible Termination
Marking:	No
AEC-Q200:	No
Miscellaneous:	Note: Referee time for X7R dielectric for this part number is 1000 hours. X7R dielectric is not recommended for AC line filtering or pulse applications
Chip Size:	1812
Shelf Life:	78 Weeks
MSL:	1

Specifications		
Capacitance:	330000 pF, 1kHz 1.0Vrms	
Capacitance Tolerance:	10%	
Voltage DC:	500 VDC	
Dielectric Withstanding Voltage:	750 VDC	
Temperature Range:	-55/+125°C	
Temperature Coefficient:	X7R	
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC):	15%, 1kHz 1.0Vrms	
Dissipation Factor:	2.50% 1kHz 1.0Vrms	
Aging Rate:	3% Loss/Decade Hour	
Insulation Resistance:	303 MOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.





单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET Electronics(基美)