

KEMET Part Number: MMC16.5125J100C31TV44
(F160ZS125J100Y)

MMC/F160, Film, Metallized Polyester, General Purpose, 1.2 uF, 5%, 63 VAC, 100 VDC, 100°C, 6560, 7mm



Note: 'Y' correspond to the letters used in the product bulletin

| Dimensions | |
|------------|-----------------|
| Chip Size | 6560 |
| L | 16.5mm +/-0.2mm |
| W | 15mm +/-0.2mm |
| T | 7mm +/-0.2mm |
| F | 0.5mm NOM |

| Packaging Specifications | |
|--------------------------|---------------------------|
| Packaging: | T&R, Vertical Orientation |
| Packaging Quantity: | 200 |

| General Information | |
|---------------------|-------------------------------------|
| Series: | MMC/F160 |
| Dielectric: | Metallized Polyester |
| Style: | SMD Chip |
| RoHS: | Yes |
| Miscellaneous: | Not For New Design. Use Series F161 |

| Specifications | |
|------------------------|-----------------------|
| Capacitance: | 1.2 uF |
| Capacitance Tolerance: | 5% |
| Voltage AC: | 63 VAC |
| Voltage DC: | 100 VDC |
| Temperature Range: | -55/+100C |
| Rated Temperature: | 100°C |
| Dissipation Factor: | 0.8% 1kHz, 1.5% 10kHz |
| Insulation Resistance: | 4.1667 GOhms |
| Max dV/dt: | 8 V/us |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET Electronics\(基美\)](#)