

**KEMET Part Number: MMC7.3124K100K33TR12**  
(F160SL124K100V)

MMC/F160, Film, Metallized Polyester, General Purpose, 0.12 uF, 10%, 63 VAC, 100 VDC, 100°C, 2824, 3mm



Note: '()' correspond to the letters used in the product bulletin

| Dimensions |                |
|------------|----------------|
| Chip Size  | 2824           |
| L          | 7.3mm +/-0.2mm |
| W          | 6mm +/-0.2mm   |
| T          | 3mm +/-0.2mm   |
| F          | 0.5mm NOM      |

| Packaging Specifications |      |
|--------------------------|------|
| Packaging:               | T&R  |
| Packaging Quantity:      | 2500 |

| General Information |  |
|---------------------|--|
| Series:             | MMC/F160   |
| Dielectric:         | Metallized Polyester                                 |
| Style:              | SMD Chip   |
| RoHS:               | Yes  |
| Miscellaneous:      | Not For New Design. Use F161SL124K100V (Series F161) |

| Specifications         |  |
|------------------------|--|
| Capacitance:           | 0.12 uF                                  |
| Capacitance Tolerance: | 10%                                      |
| Voltage AC:            | 63 VAC                                   |
| Voltage DC:            | 100 VDC                                  |
| Temperature Range:     | -55/+100C                                |
| Rated Temperature:     | 100°C                                    |
| Dissipation Factor:    | 0.80% 1kHz, 1.20% 10kHz,<br>3.00% 100kHz |
| Insulation Resistance: | 15 GOhms                                 |
| Max dV/dt:             | 30 V/us                                  |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET Electronics\(基美\)](#)