

KEMET Part Number: PHE450HR7820JR06L2 Not for New Design
(F450RS825J250Z)

PHE450/F450, Film, Double Metallized Polypropylene, General Purpose, 8.2 uF, 5%, 250 VDC, 85°C, Lead Spacing = 37.5mm



| General Information | |
|---------------------|---|
| Series: | PHE450/F450 |
| Dielectric: | Double Metallized Polypropylene |
| Style: | Radial |
| Features: | Pulse |
| RoHS: | Yes |
| Lead: | Wire Leads |
| AEC-Q200: | No |
| Miscellaneous: | The Rated Voltage Decreases 1.3%/C Between +85C And +105C. Rthha= 17 C/W (85C), 0.2 m/s |

| Dimensions | |
|------------|--------------------|
| L | 41mm MAX |
| H | 43mm MAX |
| T | 28mm MAX |
| S | 37.5mm +0.4/-0.4mm |
| LL | 18.5mm +0.5mm |
| F | 1mm +/-0.05mm |
| G | 0.5mm NOM |

| Specifications | |
|------------------------|-------------------------------|
| Capacitance: | 8.2 uF |
| Capacitance Tolerance: | 5% |
| Voltage AC: | 180 VAC |
| Voltage DC: | 250 VDC (85C), 185 VDC (105C) |
| Temperature Range: | -55/+105°C |
| Rated Temperature: | 85°C |
| Dissipation Factor: | 0.03% 1kHz |
| Insulation Resistance: | 3.659 GOhms |
| Max dV/dt: | 200 V/us |
| Inductance: | 6 nH |

| Packaging Specifications | |
|--------------------------|------------|
| Packaging: | Pizza, Box |
| Packaging Quantity: | 54 |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET Electronics\(基美\)](#)