
KEMET Part Number: PFR5151H250J11L16.5TR18

(F411JH151H250L)



PFR/F411, Film, Film/Foil Polypropylene, 150 pF, 2.5%, 250 VDC, 85°C, Lead Spacing = 5mm



General Information			
Series:	PFR/F411		
Dielectric:	Film/Foil Polypropylene		
Style:	Radial		
Features:	Pulse		
RoHS:	Yes		
Lead:	Wire Leads		
Miscellaneous:	An Operating Temperature Up To +105C Is Allowed Under Certain Conditions. Please Consult KEMET For Details.		

Specifications

Dimensions			
L	7.2mm MAX		
Н	6mm MAX		
Т	4.5mm MAX		
S	5mm +0.6/-0.1mm		
Н0	18.5mm +/-0.5mm		
F	0.5mm +/-0.05mm		
G	0.5mm NOM		

IICIISIOIIS		- P • • • • • • • • • • • • • • • • • • •	
7.2mm MAX	Capaci	itance:	150 pF
6mm MAX	Capacitance Tole	rance:	2.5%
4.5mm MAX	Volta	ge AC:	160 VAC
5mm +0.6/-0.1mm	Voltag	ge DC:	250 VDC
18.5mm +/-0.5mm	Temperature F	Range:	-55/+100C
0.5mm +/-0.05mm	Rated Temper	rature:	85°C
0.5mm NOM	Dissipation F	actor:	0.04% 1kHz, 0.04% 10kHz, 0.05% 100kHz
	Insulation Resis	tance:	200000 GOhms
a Cassifications	Max	dV/dt:	1000 V/us
g Specifications	Induc	tance:	6 nH

Packaging Specifications		
Packaging:	T&R	
Packaging Quantity:	1500	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET Electronics(基美)