

ALS32, Aluminum Electrolytic, 3,900 uF, 20%, 400 VDC, -40/+85°C



Dimensions	
D	63.5mm +/-0.8mm
L	130.2mm +/-1.6mm
T	5.5mm +/-0.5mm
S	28.5mm +/-0.5mm
DT	13mm +/-0.5mm
TD	10mm MIN
V	15.8mm NOM

Packaging Specifications	
Weight:	600 g
Packaging:	Bulk, Box

General Information	
Series:	ALS32
Dielectric:	Aluminum Electrolytic
Description:	Screw Terminal, Aluminum Electrolytic
RoHS:	Yes
AEC-Q200:	No
Notes:	Add 0.4mm To D (1.1mm When D = 88.9) And 1.1mm To L For Sleeving. Dimension LT Available On Request. MS (MxH) = M12x16. Mounting Clip (Sold Separately): V8
Shelf Life:	156 Weeks

Specifications	
Capacitance:	3,900 uF
Capacitance Tolerance:	20%
Voltage DC:	400 VDC, 440 VDC (Surge)
Temperature Range:	-40/+85°C
Rated Temperature:	85°C
Life:	19000 Hrs (Rated Voltage And Ripple Current At 85C), 38000 Hrs (Rated Voltage At 85C)
Resistance:	37 mOhms (120Hz 25C), 25 mOhms (20kHz 25C)
Ripple Current:	14.6 Amps (120Hz 85C), 22.1 Amps (20kHz 85C)
Leakage Current:	6000 uA (5min 20°C)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET Electronics\(基美\)](#)