


PEH126, Aluminum Electrolytic, 600 uF, -10/+30%, 40 VDC, -40/+150°C



Dimensions	
D	16mm +/-0.5mm
L	35.5mm +/-1mm
LL	3.3mm +/-0.5mm
F	1mm +/-0.3mm

Packaging Specifications	
Weight:	11 g
Packaging:	Bulk, Bag
Packaging Quantity:	100

General Information	
Series:	PEH126
Dielectric:	Aluminum Electrolytic
Style:	Radial Crown
Description:	Radial Crown Aluminum Electrolytic
RoHS:	Yes
Lead:	Radial Crown
Qualifications:	AEC-Q200
AEC-Q200:	Yes
Miscellaneous:	Note: The Voltage, Life , And Ripple Current Rating Displayed For This Series Is Rated At 125C Instead Of 150C
Shelf Life:	156 Weeks

Specifications	
Capacitance:	600 uF
Capacitance Tolerance:	-10/+30%
Voltage DC:	40 VDC
Temperature Range:	-40/+150°C
Rated Temperature:	150°C
Life:	6300 Hrs
Resistance:	120 mOhms (100Hz 20C), 30 mOhms (100kHz 20C)
Ripple Current:	1.4 Amps (100Hz 125C), 8.3 Amps (5kHz 105C), 4.9 Amps (5kHz 125C), 1.9 Amps (5kHz 150C)
Leakage Current:	72 uA (5min 20°C)
Inductance:	12 nH (ESL)

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)