
## KEMET Part Number: MDK10685K100A58P7TUBE

(F687AA685K100T)



MDK/F68, Film, Metallized Polyester, Dual-In-Line, 6.8 uF, 10%, 63 VAC, 100 VDC, 85°C, 10mm



General Information	
Series:	MDK/F68
Dielectric:	Metallized Polyester
Style:	Dual-In-Line
RoHS:	Yes
Lead:	Wire Leads
AEC-Q200:	No

Dimensions	
L	23mm +/-0.2mm
L2	3.88mm MAX
W	12.7mm +/-0.2mm
Н	11mm +/-0.2mm
H1	14.2mm +1mm
S	10mm +/-0.2mm
S1	2.54mm +/-0.2mm
S2	15.24mm +/-0.2mm
LL	3.2mm +1mm
F	0.5mm +/-0.05mm
E	0.2mm MAX
G	0.3mm MAX
Х	0.35mm +/-0.05mm

Specifications		
Capacitance:	6.8 uF	
Capacitance Tolerance:	10%	
Voltage AC:	63 VAC	
Voltage DC:	100 VDC	
Temperature Range:	-55/+125°C	
Rated Temperature:	85°C	
Dissipation Factor:	0.80% 1kHz 1.50% 10kHz	
Insulation Resistance:	735.3 MOhms	
Inductance:	4 nH	

Packaging Specifications		
Packaging:	Tube	
Packaging Quantity:	21	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generate



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)