
KEMET Part Number: C44PKGR6150AASJ



C44P, Film, Metallized Polypropylene, AC Filter, 150 uF, 5%, 440 VAC, 1000 VDC



Dimensions		
D	65mm +/-0.5mm	
L	247mm +/-2mm	
W	18mm +/-1mm	
S	28mm +/-1mm	

Packaging Specifications		
Mounting:	Bolt - M12x16	
Packaging:	Bulk, Bag	

General Information		
Series:	C44P	
Dielectric:	Metallized Polypropylene	
Style:	Can	
Features:	Single Phase PFC	
RoHS:	Yes	
Lead:	Threaded Studs M10	
Miscellaneous:	Thermal Resistance = 3.5 C/W	

Specifications	
Capacitance:	150 uF
Capacitance Tolerance:	5%
Voltage AC:	440 VAC
Voltage DC:	1000 VDC
Temperature Range:	-25/+70C
Rated Temperature:	70°C
Insulation Resistance:	10 MOhms
Max dV/dt:	20 V/us
Resistance:	2.8 mOhms (10kHz)
Ripple Current:	45 Amps (10kHz 40C)
Inductance:	160 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)