

R47_X1, Film, Metallized Polypropylene, Automotive Safety, 0.047 uF, 10%, 440 VAC (X1), 1000 VDC, 110°C, Lead Spacing = 15mm



Dimensions

| | |
|----|-----------------|
| L | 18mm +0.3mm |
| H | 17.5mm +0.1mm |
| T | 6mm +0.2mm |
| S | 15mm +/-0.4mm |
| LL | 25mm +2/-1mm |
| F | 0.6mm +/-0.05mm |

Packaging Specifications

| | |
|----------------------------|-----------|
| Packaging: | Bulk, Bag |
| Packaging Quantity: | 700 |

General Information

| | |
|------------------------|------------------------------|
| Series: | R47_X1 |
| Dielectric: | Metallized Polypropylene |
| Style: | Radial |
| Features: | Automotive Grade, EMI Safety |
| RoHS: | Yes |
| Lead: | Wire Leads |
| Qualifications: | AEC-Q200, ENEC, UL, cUL |
| AEC-Q200: | Yes |

Specifications

| | |
|-------------------------------|--------------|
| Capacitance: | 0.047 uF |
| Capacitance Tolerance: | 10% |
| Voltage AC: | 440 VAC (X1) |
| Voltage DC: | 1000 VDC |
| Temperature Range: | -40/+110C |
| Rated Temperature: | 110°C |
| Dissipation Factor: | 0.10% 1kHz |
| Insulation Resistance: | 100 GOhms |
| Max dV/dt: | 600 V/us |
| Safety Class: | X1 |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)