
KEMET Part Number: MPC1040LR88C Not for New Design

(UPIA1040LR88C0)



KEMET, MPC, Power, 880 nH, 20%



General Information		
Series:	MPC	
Style:	SMD	
Description:	Shielded, Surface Mount Inductor	
Features:	High Speed, Large Current DC/ DC Converter	
RoHS:	Yes	
Core:	Composite	

Dimensions		
Chip Size	4539	
L	11.5mm MAX	
W	10mm +/-0.3mm	
Т	4mm MAX	
LL	2.1mm NOM	
G	3mm +/-0.5mm	

Specifications	
Inductance:	0.88 uH (0.1 MHz)
Inductance Tolerance:	20%
Temperature Range:	-40/+125C
Rated Temperature:	120°C
Shielded:	Yes
Current:	24 Amps (Isat, 20% Drop In Inductance), 17 Amps (Irms, 40C Rise By Self Heating)
DC Resistance:	2.3 mOhms

Packaging Specifications	
Packaging:	T&R, 330mm
Packaging Quantity:	500

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)