
## KEMET Part Number: MDK10683J630A54P4TUBE

(F684AA683J630T)



MDK/F68, Film, Metallized Polyester, Dual-In-Line, 0.068 uF, 5%, 220 VAC, 630 VDC, 85°C, 10mm



General Information	
Series:	MDK/F68
Dielectric:	Metallized Polyester
Style:	Dual-In-Line
RoHS:	Yes
Lead:	Wire Leads
AEC-Q200:	No

Dimensions		
בוווכווסוטווס		
L	13.5mm +/-0.2mm	
L2	2.94mm MAX	
W	12.2mm +/-0.2mm	
Н	6.05mm +/-0.2mm	
H1	9.25mm +1mm	
S	10mm +/-0.2mm	
S1	2.54mm +/-0.2mm	
S2	7.62mm +/-0.2mm	
LL	3.2mm +1mm	
F	0.5mm +/-0.05mm	
E	0.2mm MAX	
G	0.3mm MAX	
Х	0.35mm +/-0.05mm	

Packaging Specifications	
Packaging:	Tube
Packaging Quantity:	35

Specifications	
Capacitance:	0.068 uF
Capacitance Tolerance:	5%
Voltage AC:	220 VAC
Voltage DC:	630 VDC
Temperature Range:	-55/+125°C
Rated Temperature:	85°C
Dissipation Factor:	0.80% 1kHz 1.50% 10kHz 2.50% 100kHz
Insulation Resistance:	30 GOhms
Inductance:	4 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.





单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)