
KEMET Part Number: PFR5151H400J11L4BULK

(F411JH151H400C)



PFR/F411, Film, Film/Foil Polypropylene, 150 pF, 2.5%, 400 VDC, 85°C, Lead Spacing = 5mm



General Information		
Series:	PFR/F411	
Dielectric:	Film/Foil Polypropylene	
Style:	Radial	
Features:	Pulse	
RoHS:	Yes	
Lead:	Wire Leads	
Miscellaneous:	An Operating Temperature Up To +105C Is Allowed Under Certain Conditions. Please Consult KEMET For Details.	

Specifications

Dimensions		
L	7.2mm MAX	
Н	6mm MAX	
Т	4.5mm MAX	
S	5mm -0.4mm	
LL	4mm +1mm	
F	0.5mm +/-0.05mm	
G	0.5mm NOM	

Capacitance: 150 pF	Сар	7.2mm MAX	L
acitance Tolerance: 2.5%	Capacitance T	6mm MAX	Н
Voltage AC: 220 VAC	Vo	4.5mm MAX	Т
Voltage DC: 400 VDC	Vo	5mm -0.4mm	S
emperature Range: -55/+100C	Temperatu	4mm +1mm	LL
Rated Temperature: 85°C	Rated Tem	0.5mm +/-0.05mm	F
Dissipation Factor: 0.04% 1kHz 0.05% 100k	Dissipatio	0.5mm NOM	G
ulation Resistance: 200000 GO	Insulation Re		
Max dV/dt: 1000 V/us	M	Packaging Specifications	
Inductance: 6 nH	Inc		

Packaging Specifications	
Packaging:	Bulk
Packaging Quantity:	1000

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information of otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Downloaded From Oneyac.com



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)